


- | | |
|---|---|
| (1) CONCRETE DECK | (9) 50X50 MM MORTAR CANT STRIP |
| (2) SLOPED CONCRETE | (10) BASE FLASHING |
| (3) VAPOR BARRIER | (11) 20X20 MM GROOVE, POINTED WITH BITUMEN MASTIC |
| (4) THERMAL INSULATION ,50MM | (12) TILTED TILE |
| (5) MBM WATERPROOFING | |
| (6) FILTER FABRIC SEPARATION LAYER 200 G/M ² | |
| (7) SAND & MORTAR BED | |
| (8) TILES, AS SPECIFIED | |

NOTES :

1- MEMBRANE BASE FLASHING TERMINATION SHALL BE MIN. 100 MM ABOVE ROOF FINISH LEVEL.

(USE "SYSTEM REFERENCE" TO OBTAIN RELEVANT DETAILS FROM "STANDARD CONSTRUCTION DETAILS" SECTION)

	Application	ROOFING APPLICATIONS	RC11
	Deck Type	CONCRETE DECK - FLAT ROOFS	
	Use	ACCESSIBLE	
	Finish	PROTECTED WITH TILES , MARBLE OR AS SPECIFIED	REFERENCE:
	Assembly	CONVENTIONAL ROOF MEMBRANE ASSEMBLY	BNTS/03/RC11
50, Al Khalifa Al Maamoun St., Roxy, Heliopolis, Cairo - Egypt.		E-mail: bitunil@bitunil.com	DATE:
TEL 202 451 1104 - 202 451 1105 FAX 202 451 1108		Web Site: www.bitunil.com	NOVEMBER 2014