



- | | |
|--|---|
| (1) CONCRETE DECK | (4) "BITUFLASH-RS 200" REINFORCING STRIP |
| (2) LEVELLING SCREED (IF REQUIRED) | (5) "BITUFLASH-FM" BASE FLASHING |
| (3A) MBM WATERPROOFING BASE LAYER | (6) COUNTER FLASHING SYSTEM ALUMINIUM & SEALANT |
| (3B) MBM SELF PROTECTED WATERPROOFING MAIN LAYER | |

NOTES :

- 1- IF SUBSTRATE IS PRESENTING A ROUGH SURFACE, A LEVELLING SCREED 20-30 MM SHALL BE REQUIRED.
 2- MEMBRANE LAYERS SHALL BE APPLIED FULLY BONDED, AND SECURED BY MECHANICAL FASTENING AT THE TOP OF EDGES BY COUNTER FLASHING SYSTEM.

(USE "SYSTEM REFERENCE" TO OBTAIN RELEVANT DETAILS FROM "STANDARD CONSTRUCTION DETAILS" SECTION)

	Application	ROOFING APPLICATIONS	RC50
	Deck Type	CONCRETE DECK - PITCHED ROOFS	
	Use	NON-ACCESSIBLE	
	Finish	EXPOSED (MBM SELF-PROTECTED MEMBRANE)	REFERENCE: BNTS/03/RC50
	Assembly	NON-INSULATED	DATE: NOVEMBER 2011
50, Al Khalifa Al Maamoun St., Roxy, Heliopolis, Cairo - Egypt.		E-mail: bitunil@bitunil.com	
TEL : 202 451 1104 - 202 451 1105 FAX: 202 451 1108		Web Site: www.bitunil.com	