



- (1) CONCRETE DECK
- (2) SLOPED CONCRETE
- (3) MBM WATERPROOFING
- (4) POLYPROPELENE MOISTURE RETENTION MAT, 450 GM/M2
- (5) DRAINGE CELL 25MM
- (8) FILTER LAYER 200 GM/M2
- (7) ENGINEERED SOIL
- (8) PLANTATION
- (9) GRAVEL LAYER
- (10) 50X50MM MORTAR CANT STRIP
- (11) BASE FLASHING
- (12) 20X20MM GROOVE, POINTED WITH BITUMEN MASTIC

NOTES :

- 1- MEMBRANE BASE FLASHING TERMINATION SHALL BE MIN. 150 MM ABOVE FINISH LEVEL.
- 2- WATER PROOFING MEMBRANE SHALL BE RESISTANT TO ROOT PENETRATION " BITUGARDEN"

	Application	Water Proofing Applications	MG 10
	Deck Type	CONCRETE DECK - FLAT ROOFS	
	Use	EXTENSIVE/ SEMI INTENSIVE GREEN ROOF	
	Finish	PLANTATION & HARD LANDSCAPE	REFERENCE: BNTS/03/RC10
	Assembly	NON- INSULATED ROOF	DATE: NOVEMBER 201.
50, Al Khalifa Al Maamoun St., Roxy, Heliopolis, Cairo - Egypt.		E-mail: bitunil@bitunil.com	
TEL : (202) 24511104 - (202) 24511105		FAX : (202) 24511108	Web Site: www.bitunil.com