



- |                                   |   |
|-----------------------------------|---|
| (1) CONCRETE DECK                 | (6) 50X50 MM MORTAR CANT STRIP                      |
| (2) SLOPED CONCRETE               | (7) "BITUFLASH-FM" BASE FLASHING                    |
| (3) MBM WATERPROOFING             | (8) COUNTER FLASHING SYSTEM,<br>ALUMINIUM & SEALANT |
| (4) SEPARATION<br>LAYER 200 GM/M2 |   |
| (5) CONCRETE SLABS                |   |

#### NOTES :

- 1- FOR LIGHT SERVICEABLE ROOFS CONCRETE SLABS MAY BE REPLACED WITH 400X400X40 MM , LOOSELY LAID ON SPECIAL PAVERS WITH OPEN JOINTS.
- 2- THIS SYSTEM IS IDEAL FOR HEAVY DUTY SERVICEABLE ROOFS.
- 3- MEMBRANE BASE FLASHING TERMINATION SHALL BE MIN. 100 MM ABOVE ROOF FINISH LEVEL.

( USE "SYSTEM REFERENCE" TO OBTAIN RELEVANT DETAILS FROM "STANDARD CONSTRUCTION DETAILS" SECTION )

	<b>Application</b>	<b>ROOFING APPLICATIONS</b>	<b>RC22</b>
	<b>Deck Type</b>	<b>CONCRETE DECK - FLAT ROOFS</b>	
	<b>Use</b>	<b>NON-ACCESSIBLE</b>	
	<b>Finish</b>	PROTECTED WITH CONCRETE SLAB / SCREED , WITH JOINTS	REFERENCE:
	<b>Assembly</b>	NON-INSULATED	BNTS/03/RC22
50, Al Khalifa Al Maamoun St., Roxy, Heliopolis, Cairo - Egypt.		E-mail: bitunil@bitunil.com	DATE:
TEL : 202 451 1104 - 202 451 1105 FAX: 202 451 1108		Web Site: www.bitunil.com	NOVEMBER 2014