



- | | |
|--|--|
| (1) CONCRETE DECK | (7) 50X50MM MORTAR CANT STRIP |
| (2) SLOPED CONCRETE | (8) "BITUFLASH-FM" BASE FLASHING |
| (3) MBM WATERPROOFING | (9) 20X20MM GROOVE, POINTED WITH SEALANT |
| (4) "FILTONIL" FILTER FABRIC , 500 GM/M2 | |
| (5) "SEPANIL" SEPARATION LAYER 200 MICRONS | |
| (6) REINFORCED CONCRETE JOINTED SLABS | |

NOTES :

- 1- IF DECK IS FINISHED WITH ASPHALT WEARING COARSE, FINE ROUNDED AGGREGATE SHALL BE USED, ASPHALT SHALL BE POURED DIRECTLY ONTO THE MEMBRANE SYSTEM AT 140°C AND COMPACTED WITH A HAND ROLLER.
- 2- IF DECK IS FINISHED WITH "INTERLOCK" TILES, A LAYER OF SAND ON "SEPANIL" 300 MICRONS SHALL RECEIVE THE TILES.
- 3- SEALANT USED FOR ALL JOINTS SHALL BE OF A GOOD QUALITY THAT RESISTS OILS, PETROLEUM, GREASE, ...ETC.

(USE "SYSTEM REFERENCE" TO OBTAIN RELEVANT DETAILS FROM "STANDARD CONSTRUCTION DETAILS" SECTION)

	Application	MISCELLANEOUS APPLICATIONS	MP10
		CAR PARKS (MULTI-STORY)	
	Conditions	COVERED WITH REINFORCED CONCRETE SLABS	
System	MBM WATERPROOFING PARKING DECK SYSTEM	REFERENCE: BNTS/03/MW10	
50, Al Khalifa Al Maamoun St., Roxy, Heliopolis, Cairo - Egypt. TEL.: 202 451 1194 - 202 451 1195 FAX: 202 451 1198		E-mail: bitunil@bitunil.com Web Site: www.bitunil.com	DATE: NOVEMBER 2014