



- | | |
|---|--|
| (1) CONCRETE DECK | (7) 50X50 MM MORTAR CANT STRIP |
| (2) SLOPED LEVELLING
SCREED | (8) MBM BASE FLASHING |
| (3) MBM WATERPROOFING | (9) 20X20 MM GROOVE, POINTED
WITH SEALANT |
| (4) "SIPANIL" SEPARATION
LAYER 300 GM/M2 | (10) METAL LATH |
| (5) 20-30 MM SCREED | |
| (6) TILES ON MORTAR BED | |

NOTES :

- 1- FLOOR FINISH AND TREATMENT MAY CHANGE DUE TO PARTICULAR USE OF SPACE.
- 2- A POLYETHYLENE CLOSED CELL SHEET 3 MM THICK. PHONIC SCREEN MAY BE LAID DIRECTLY ONTO THE MEMBRANE SYSTEM (IF REQUIRED).
- 3- IF "BITUFLASH-FM" IS USED AS A BASE FLASHING, IT CAN DIRECTLY RECEIVE TILES FIXING MORTAR WITH A BONDING AGENT.

(USE "SYSTEM REFERENCE" TO OBTAIN RELEVANT DETAILS FROM "STANDARD CONSTRUCTION DETAILS" SECTION)

	Application	MISCELLANEOUS APPLICATIONS	MW10
		WET & MECHANICAL ROOMS	
	Conditions	AREAS WITH HUMID & WET CONDITIONS	
	System	MBM WATERPROOFING WET ROOMS SYSTEM	REFERENCE: BNTS/03/MW10
	50, Al Khalifa Al Maamoun St., Roxy, Heliopolis, Cairo - Egypt. TEL 202 451 1104 - 202 451 1105 FAX 202 451 1108	E-mail: bitunil@bitunil.com Web Site: www.bitunil.com	DATE: NOVEMBER 2014